



## FEATURES

- 34 mm compression drivers
- Steel frame woofers
- PTC thermistor protected tweeter
- Black carpet finish
- 15 mm reinforced cabinet
- Speakon® and 1/4" inputs
- All metal handles with stamped CV logo

The Intense series from Cerwin-Vega! has established a well-deserved reputation for providing extraordinary and impactful sound at an affordable price. How do you enhance a leading product in its class? Improve the product components, sound quality AND lower the price! Introducing the new Intense! V2. Perfect for PA applications such as live sound, program playback, and DJ systems -- it can be installed in facilities, venues and clubs – yet it is fully portable for sound on the go.

### ***So what's New?***

**Stronger drivers** by beefing up the build quality with the addition of more steel.

**Enhanced durability** by upgrading the cabinet construction with internal bracing.

**Better performance** is achieved by increasing the size of the magnets on the compression drivers.

**Improved dependability** from a new positive temperature coefficient (PTC) thermistor that protects the tweeter. This component acts as a self-repairing fuse allowing the speaker to return to normal operation once the input fault is corrected.

Run longer. Run louder. Run with Cerwin-Vega!

Specifications & appearance subject to change.

USA: P 954.949.9600 • F 954.949.9590

EUROPE: P +32.2.645.05.00 • F +32.2.645.05.05

## SPECIFICATIONS

|  | <b>INT-152 V2</b>  | <b>INT-252 V2</b>  | <b>INT-118s V2</b>                            |
|--|--|--|---|
| <b>Frequency Response</b><br>(1W /1M)  | +/- 3 dB 64 Hz - 19.8 kHz<br>-10 dB 46 Hz                          | +/- 3 dB 57 Hz - 19.8 kHz<br>-10 dB 44 Hz                          | +/- 3 dB 49 Hz - 200 kHz<br>-10 dB 33.5 Hz    |
| <b>Nominal Impedance (Ohms)</b>  | Full Range 8 Ohms  | Full Range 4 Ohms  | Full Range 8 Ohms                             |
| <b>Axial Sensitivity</b><br>(dB SPL, 1W / 1M)  | Full Range 95 dB   | Full Range 94 dB   | Full Range 96 dB                              |
| <b>Calculated Maximum Output</b><br>(dB SPL, @ 1M)                                     | Full Range 124 dB  | Full Range 125 dB  | Full Range 125.5 dB                           |
| <b>Power Handling (Watts)</b>  | RMS 200 W<br>Program 400 W<br>Peak 800 W                           | RMS 350 W<br>Program 700 W<br>Peak 1400 W                          | RMS 225 W<br>Program 450 W<br>Peak 900 W      |
| <b>Nominal Coverage Angles /<br/>-6 dB points (Degrees)</b>                            | Horizontal 90°<br>Vertical 50°                                     | Horizontal 90°<br>Vertical 50°                                     | Horizontal N/A<br>Vertical N/A                |
| <b>Dimensions</b><br><b>152 &amp; 252 (H x WF x WB x D)</b><br><b>118s (H x W x D)</b> | 30.75" x 18.5" x 10.375" x 19.25"<br>781mm x 470mm x 264mm x 489mm | 46.5" x 18.5" x 10.375" x 19.25"<br>1181mm x 470mm x 264mm x 489mm | 25.5" x 23.75" x 23"<br>648mm x 603mm x 584mm |
| <b>Weight (Lbs / Kg)</b>   | 57.70 Lbs. / 26.2 Kg   | 87.20 Lbs. (39.5 Kg)   | 88.85 Lbs. / 40.3 Kg                          |

Specifications & appearance subject to change.

USA: P 954.949.9600 • F 954.949.9590

EUROPE: P +32.2.645.05.00 • F +32.2.645.05.05